




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification⁶ : B41J 2/16, 2/14, 2/045</p>	<p>A2</p>	<p>(11) International Publication Number: WO 98/52763</p> <p>(43) International Publication Date: 26 November 1998 (26.11.98)</p>
<p>(21) International Application Number: PCT/GB98/01495</p> <p>(22) International Filing Date: 22 May 1998 (22.05.98)</p> <p>(30) Priority Data: 9710530.8 23 May 1997 (23.05.97) GB</p> <p>(71) Applicant (for all designated States except US): XAAR TECHNOLOGY LIMITED [GB/GB]; Science Park, Cambridge CB4 4FD (GB).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): TEMPLE, Stephen [GB/GB]; 66 Girton Road, Cambridge CB3 0LN (GB).</p> <p>(74) Agents: MOIR, Michael, Christopher et al.; Mathys & Squire, 100 Grays Inn Road, London WC1X 8AL (GB).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>Without international search report and to be republished upon receipt of that report.</i></p>

(54) Title: DROPLET DEPOSITION APPARATUS AND METHODS OF MANUFACTURE THEREOF



(57) Abstract

Droplet deposition apparatus comprising first and second channels (82a, 82b), one end of each channel communicating with a single, common supply chamber (40) for supply of droplet liquid and the respective other ends of the first and second channels each communicating with a respective further supply chamber (88, 92) for supply of droplet liquid; each of said first and second channels having an opening (96a, 96b) for ejection of droplets therefrom; and actuator means being associated with each channel for effecting the ejection of droplets.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Droplet Deposition Apparatus and Methods of Manufacture thereof

The present invention relates to droplet deposition apparatus, in particular an inkjet printhead.

Figure 1 shows an inkjet printhead of the kind disclosed in WO91/17051 and made up of a body formed with an array of open-topped channels which are closed by a cover. Each channel is connected at either end to a respective ink supply chamber and at its middle to a nozzle formed in the cover. The channel walls comprise piezoelectric material that deflects when subjected to an electric field and causes the ejection of an ink droplet from the respective nozzle.

Preferred forms of the present invention have as an objective a device of the kind described above which is simple and cheap to manufacture.

In one aspect the invention comprises droplet deposition apparatus comprising: a body formed with at least one channel open on one side, the channel communicating at each end with a supply chamber for supply of droplet fluid, actuator means being associated with each channel for effecting ejection of droplets; a cover closing the open side of the at least one channel and having formed therein at least one opening for ejection of droplets from the channel; and a base defining with the cover the supply chambers communicating with the respective ends of the at least one channel.

In such a construction, ink supply chambers that are defined by the base and cover require less critical tolerances than when they are formed in the "active" body, as in WO91/17051. Furthermore, the base can be made of a material that is less expensive than that from which the body – the "active" component in the printhead – is formed.

A second aspect of the invention involves the control means of inkjet printheads and comprises droplet deposition apparatus comprising: a body formed with at least one chamber open on one side, each chamber communicating with an opening for ejection of droplets therefrom and with a manifold for supply of droplet fluid, actuator means being associated with each chamber for effecting ejection of droplets in response to electrical signals and a cover closing the open side of the at least one chamber; the manifold being defined at least in part by a base, the base also defining at least in part a further chamber, control means for supplying the electrical signals to the actuator means being located in the further chamber.

In this fashion, the control means - generally an integrated circuit - is itself integrated into the printhead construction, thereby increasing compactness and reducing the exposure of the integrated circuit to the environment.

In a third aspect, the present invention consists in droplet deposition apparatus comprising first and second channels, one end of each channel communicating with a single, common supply chamber for supply of droplet liquid and the respective other ends of the first and second channels each communicating with a respective further supply chamber for supply of droplet liquid; each of said first and second channels having an opening for ejection of droplets therefrom; and actuator means being associated with each channel for effecting the ejection of droplets.

Such an arrangement results in a compact construction in which droplet fluid can be passed from the single, common liquid supply chamber, through each of the first and second channels, and out into the respective further liquid supply chamber. Flow can also take place in the reverse direction. Such circulation can serve a number of purposes that are known per se, e.g. removal of dirt and air bubbles, cooling of the channel.

According to a fourth aspect, the invention consists in droplet deposition apparatus comprising a body formed with at least one chamber having an open side, each chamber communicating with a supply of droplet fluid and an opening

for ejection of droplets therefrom; actuator means being associated with each chamber for effecting ejection of droplets in response to electrical signals, a support member for said body, the support member closing the open side of said chamber and having at least one track thereon for conveying electrical signals to respective actuator means, and having formed therein at least one opening for ejection of droplets from respective chambers.

This configuration has been found to be particularly suited to manufacture: the support member is not merely a support during manufacture for the active body components – and, advantageously, drive chips mounted on the conductive tracks – it also provides location for each nozzle associated with each chamber in the bodies. An associated method is also comprised within the present invention.

A fifth aspect of the invention relates to a substrate having electrically conductive tracks, there being a plurality of locations along each track at which an integrated circuit may be connected; the plurality of locations being spaced relative to one another along each track such that, for each track, a location lying adjacent a connection to an integrated circuit die falls outside the footprint of the integrated circuit die.

In the event of a mounted integrated circuit – particularly a printhead drive chip – proving faulty, this measure allows a replacement chip to be connected to tracks on a substrate without having to remove the faulty chip, with the potential damage to the substrate that removal implies. Manufacturing yield benefits correspondingly. An associated method is also comprised within the present invention.

Advantageous embodiments of the aforementioned aspects are set out in the dependent claims (which are incorporated by reference here as consistory clauses) and in the description that follows.

The invention will now be described by way of example with reference to the following drawings, in which:

Figure 1 shows a prior art inkjet printhead of the kind disclosed in WO91/17051;

Figure 2 is a sectional view taken along line A-A of figure 1;

Figure 3 shows a printhead incorporating a first aspect of the present invention;

Figure 4 shows a printhead incorporating a second aspect of the present invention;

Figure 5 is an exploded perspective view of a "pagewidth" printhead according to the present invention;

Figure 6 is an assembled sectional view of the printhead of figure 5 taken normal to direction "W";

Figure 7 shows detail of a droplet ejection opening;

Figures 8 and 9 show various ways of mounting a drive chip.

Figure 1 shows a prior art inkjet printhead 1 of the kind disclosed in WO91/17051 and comprising a sheet 3 of piezoelectric material, suitably lead zirconium titanate (PZT), formed in a top surface thereof with an array of open-topped ink channels 7. As evident from figure 2, successive channels in the array are separated by side walls 13 which comprise piezoelectric material poled in the thickness direction of the sheet (as indicated by arrow P). On opposite channel-facing surfaces 17 are arranged electrodes 15 to which voltages can be applied via connections 34. As is known, e.g. from EP-A-0 364 136, application of an electric field between the electrodes on either side of a wall results in shear mode deflection of the wall into one of the flanking channels, generating a pressure pulse in that channel.

The channels are closed by a cover 25 in which are formed nozzles 27 each communicating with respective channels at the mid-points thereof. Droplet ejection from the nozzles takes place in response to the aforementioned pressure pulse, as is well known in the art. Supply of droplet fluid into the channel, indicated by arrows S in figure 2, is via two ducts 33 cut into the bottom face 35 of the sheet 3 to a depth such that they communicate with opposite ends respectively of the channels 7. A base cover plate 37 is bonded to the bottom face 35 to close the ducts.

Figure 3 shows an embodiment of a printhead according to a first aspect of the invention.

As in the conventional construction, open-topped ink channels 7 defining side walls 13 are formed in a body 40 of piezoelectric material. By means of electrodes 15 formed on opposite channel-facing surfaces of each side wall 13, electric fields can be applied to cause shear mode deflection of the wall and droplet expulsion from one of the flanking channels. The open-topped channels 7 are closed by a cover 25 on which may also be formed conductive tracks 49 for supplying voltages to respective electrodes 15. Tracks and electrodes may be connected via solder bonds as described in WO 92/22429. The cover is also formed, for each channel, with a nozzle 27 communicating with the mid-point of each channel and through which droplet expulsion takes place. Conductive tracks and associated solder bonds may have to be shaped and/or removed to accommodate such a nozzle.

In accordance with the invention, however, droplet fluid is supplied to each end of the channels 7 from a chamber 42 that is defined on two sides by a base 44, on a third side by the cover 25 and which communicates on a fourth side with the end of the channel 7. It will be apparent that the interface between the channel and the chamber in such a construction is determined simply by the channel depth. Since variations in the height of the body 40 and the thickness of the adjacent part (pedestal 46) of the base can be accommodated by flexure (up or down in the embodiment of figure 3) of the cover 25, manufacture can be carried out to looser tolerances.

Base 44 need not be made of the same material as the body, advantageously being made of a cheaper, non-active material that is nevertheless thermally matched to the piezoelectric material of the body and which has good thermal conductivity so as to carry away the heat generated in the active printhead bodies and driver chips. As shown in figure 3, chambers 42 may be deeper than body 40 so as to increase their cross-sectional area and thus the number of channels a single chamber can supply. However, the level of the pedestal 46 may

be reduced to that of the bottom of chamber 42, resulting in a rectangular-sectioned cavity in the base that can be more simply manufactured. The width of pedestal 46 can also be varied so as to be wider or narrower than the body 40.

Body 40 will generally comprise an array of channels - as is well-known e.g. from EP-A-0 278 590 - and chambers 42 will act as a common manifold for at least some of these. Apertures 48 allow supply of droplet liquid into chambers 42 from a reservoir such as a cartridge.

Base 44 may have a structural role, having cover 25 and active body 40 attached thereto, and being formed with lugs (not shown) for securing to the frame of a printer or similar.

A second aspect of the invention when applied to an inkjet printhead of the kind disclosed in WO92/22429 is illustrated in figure 4. This shows a sectional view along an open-topped ink channel 7 formed in a body 50 of piezoelectric material and closed by a substrate 62. Electrodes 15 extend over each channel-separating side wall 13 in the conventional manner but are connected at the open top 54 of the channel with a conductive track 56 formed on the substrate 62.

Advantageously, the two electrodes on the channel-facing wall surfaces defining a given channel are connected to a common track. Each track is connected to a drive circuit in the form of a microchip 64 which is itself mounted on the tracks 56 on the substrate, print data, power, etc being supplied to the chip via further tracks 66 and connector 70. A nozzle 27 formed in a nozzle plate 52 is located at one end of the channel for droplet ejection whilst a manifold 58 is located at the other end of the channel for supply of droplet liquid.

In accordance with the invention, the manifold 58 is defined by a base 60 acting in combination with the body 50. The base also defines, this time in combination with the substrate 62, a further chamber 68 in which is located the drive circuit 64. It will be appreciated that a particular advantage of such an integrated construction is the protection afforded the drive chip. Although the use of piezoelectric material for the base is not excluded - indeed body 50 and base 60

may be integral, base 60 is advantageously made from a cheaper, non-active material.

Figures 5 and 6 are exploded perspective and sectional views respectively of a "pagewide" printhead incorporating both first and second aspects referred to above and extending in a direction "W" transverse to a media feed direction P. In the sectional view of figure 6, two piezoelectric bodies 82a, 82b each having channels and electrodes as described above are closed by a substrate 86 in which openings 96a,96b for droplet ejection are formed. In accordance with the first aspect of the invention, respective supply chambers at the ends of the channels in each body, namely supply chambers 88 and 90 at either end of body 82a and supply chambers 90 and 92 at either end of body 82b, are defined between the substrate 86 and a base 80. Respective channel electrodes are connected to conductive tracks (not shown) on the substrate 86 as described with regard to figure 4. These conductive tracks also carry respective driver chips 84a and 84b located, in accordance with the second aspect of the invention, in further chambers 94a,94b defined by the base 80. Understandably, the further chambers 94a,94b are sealed from supply chambers 88 and 92.

This embodiment incorporates a third aspect of the present invention: the channel-closing substrate 86 with conductive tracks for conveying electrical signals to actuator means located in the channels and openings 96a,96b for droplet ejection acts as a support member for the bodies 82a and 82b. As will be evident from figure 5, bodies 82 and drive chips 84 are aligned and fixed to the substrate 86 - which in turn can be made to such a size as to be easy to handle during manufacture.

As illustrated in figure 5, bodies 82 may be butted together to form a single, contiguous, pagewide array of channels - described in WO91/17051 and consequently not in any further detail here - in which case the substrate 86 serves to support the individual bodies both during and after the butting process. Such

bodies may be tested before assembly, thereby reducing the chances of a complete printhead being faulty..

The substrate is suitably made of a robust material - such as aluminium nitride, INVAR or special glass AF45 - that has similar thermal expansion characteristics to the piezoelectric material of the bodies. It will be appreciated that the requirement for thermal matching between bodies and substrate is reduced where there is a gap between successive butted bodies (the gap advantageously being filled with glue bond material as mentioned in the aforementioned WO91/17051) in which case a less well thermally-matched material such as alumina can be used.

Figure 7 shows detail of a droplet ejection opening 96a formed in the substrate 86. Whilst the opening 96a itself may be formed with a taper, it is advantageous to form the tapered shape in a nozzle plate 98 mounted over the opening. Such a nozzle plate may comprise any of the readily-ablatable materials such as polyimide, polycarbonate and polyester that are conventionally used for this purpose.

Furthermore, nozzle manufacture can take place independently of the state of completeness of the rest of the printhead: the nozzle may be formed by ablation from the rear prior to assembly of the active body 82a onto the substrate 86 or from the front once the active body is in place. Both techniques are known in the art. The former method has the advantage that the nozzle plate can be replaced or the entire assembly rejected at an early stage in assembly, minimising the value of rejected components. The latter method facilitates the registration of the nozzles with the channels of the body when assembled on the substrate.

The construction of figures 5 and 6 has two rows of nozzles formed in a single nozzle plate extending over both the openings 96a,96b in substrate 86 and extending the full length of the substrate. Following the mounting of a corresponding two rows of bodies 82a,82b and drive chips 84a,84b onto the substrate 86 and suitable testing - as described, for example, in EP-A-0 376 606 -

base 80 can be attached, thereby to define manifold chambers 88,90 and 92. In accordance with a further aspect of the invention, chamber 90 supplies the ends of channels formed in both bodies 82a,82b whilst chambers 88 and 92 supply the other ends of the channels in bodies 82a, 82b respectively. Conduits through which ink is supplied from the outside of the printhead to each chamber are indicated by dashed lines at 88',90' and 92'. It will be evident that this results in a particularly compact construction in which ink can be circulated from common manifold 90, through the channels in each of the bodies (for example to remove trapped dirt or air bubbles) and out through chambers 88 and 92.

Figure 8 shows partial detail of the mounting of drive chip 84a on the substrate 86 having output tracks 120,122 which connect drive chip outputs 132,134 to actuating electrodes in the body and an input track 110 to drive chip input terminal 130. It will be understood that a drive chip will have many such inputs and outputs, there being generally at least twice as many outputs as inputs. 84a indicates the first location on the substrate 86 at which a drive chip will be placed. However, should the drive chip at this location subsequently be found to be faulty – e.g. in the course of testing as described above – a replacement chip can be mounted at location 84a' as indicated by dashed lines. If necessary, the connections of the faulty chip to the tracks 120 and 122 can be severed by cutting through the tracks at points 136 – a laser may be particularly suitable for this purpose. The beneficial effect of this measure on manufacturing yield in a pagewide printhead – which, as shown in figure 5, may have several tens of driver chips – will be evident.

Figure 9 shows another embodiment of this aspect of the invention in which input signals are supplied via a bus comprising tracks 110, etc. Connection between the tracks 110, etc. and chip input terminals 130 is achieved by means of further tracks 150, deposited on top of tracks 110, etc. and isolated therefrom by a passivation layer 145. Should drive chip (integrated circuit die) 84a prove faulty, it is possible to connect a replacement chip or die at location 84a', shown dashed in figure 9, which is spaced from (falls outside the footprint of) the first chip 84a. A second bus

comprising tracks 110', passivation layer 145' and further tracks 150' is used to supply input signals. A further passivation layer 140 underlies the second bus, isolating it from output tracks 120,122,.. which have locations for connection both to the output terminals 132,134,.. of chip 84 and to the output terminals 132',134' of replacement chip 84'. Excision by means of a laser along line 136 allows a faulty chip to be electrically isolated from the output tracks 120,122,.. before a replacement chip 84' is connected.

The foregoing examples have related particularly to droplet deposition apparatus utilising piezoelectric material operated in shear mode as the actuating mechanism. Such devices are discussed, for example, in the aforementioned WO91/17051, in EP-A-0 364 136 and US-A-5 227 813. The principles outlined above are equally applicable to other actuating mechanisms however, including both piezoelectric and thermal (bubble-jet), and in particular to the arrangements disclosed in co-pending UK patent application no. 9721555.2.

Claims

1. Droplet deposition apparatus comprising first and second channels, one end of each channel communicating with a single, common supply chamber for supply of droplet liquid and the respective other ends of the first and second channels each communicating with a respective further supply chamber for supply of droplet liquid; each of said first and second channels having an opening for ejection of droplets therefrom; and actuator means being associated with each channel for effecting the ejection of droplets.
2. Apparatus according to claim 1, wherein the longitudinal axes of the first and second ink channels are colinear.
3. Apparatus according to claim 2 and comprising a plurality of first and second ink channels each having respective openings for ejection of droplets, the plurality of openings for said plurality of first ink channels being arranged in a first linear array extending in a first array direction, and the plurality of openings for said plurality of second ink channels being arranged in a second linear array extending in a second array direction, wherein the first and second linear array directions are parallel.
4. Apparatus according to claim 3, and wherein said plurality of first and second ink channels communicate with the single, common chamber for supply of droplet liquid, the single, common chamber extending parallel to said first and second array directions.
5. Apparatus according to any preceding claim comprising a body formed with said channels open on one side; a cover closing the open side of the channels and having formed therein said openings; and a base defining the supply chambers with the cover.

6. Droplet deposition apparatus comprising: a body formed with at least one channel open on one side, the channel communicating at each end with a supply chamber for supply of droplet fluid, actuator means being associated with each channel for effecting ejection of droplets; a cover closing the open side of the at least one channel and having formed therein at least one opening for ejection of droplets from the channel; and a base defining with the cover the supply chambers communicating with the respective ends of the at least one channel.
7. Apparatus according to claim 6, wherein the actuator means are comprised in the body.
8. Apparatus according to any of claims 5 to 7, wherein the body and base are integral.
9. Apparatus according to any of claims 5 to 8, wherein the body is mounted on and supported by the base.
10. Apparatus according to any of claims 5 to 9, wherein the base defines at least in part a further chamber, control means for supplying the electrical signals to the actuator means being located in the further chamber.
11. Droplet deposition apparatus comprising: a body formed with at least one chamber open on one side, each chamber communicating with an opening for ejection of droplets therefrom and with a manifold for supply of droplet fluid, actuator means being associated with each chamber for effecting ejection of droplets in response to electrical signals and a cover closing the open side of the at least one chamber; the manifold being defined at least in part by a base, the base also defining at least in part a further chamber, control

means for supplying the electrical signals to the actuator means being located in the further chamber.

12. Apparatus according to claim 11, wherein the actuator means are comprised in the body.

13. Apparatus according to claim 11 or 12, wherein the body and base are integral.

14. Apparatus according to any of claims 11 to 13, wherein the opening for ejection of droplets is formed in the cover.

15. Apparatus according to claims 11 to 14, wherein the manifold is closed by the cover.

16. Apparatus according to claims 11 to 15, wherein the further chamber is closed by the cover.

17. Apparatus according to claims 11 to 16, wherein the control means are mounted on the cover.

18. Apparatus according to claims 5, 6 or 14, or any claim dependent therefrom, wherein the cover has at least one track thereon for conveying signals to respective actuator means.

19. Apparatus according to claim 18, wherein the cover forms a support member for the body.

20. Droplet deposition apparatus comprising a body formed with at least one chamber having an open side, each chamber communicating with a supply of droplet fluid and an opening for ejection of droplets therefrom; actuator means being associated with each chamber for effecting ejection of droplets in response to electrical signals, a support member for said body, the support member closing the open side of said chamber and having at least one track thereon for conveying electrical signals to respective actuator means, and having formed therein at least one opening for ejection of droplets from respective chambers.

21. Apparatus according to claim 20, wherein a nozzle plate is attached to the opposite surface of the support member to that to which the body is attached, there being formed in the nozzle plate a nozzle communicating with the opening in the support member for ejection of droplets.

22. Apparatus according to claim 20 or 21, wherein the support member is rigid.

23. Apparatus according to claim 22, wherein the support member comprises metal and/or ceramic.

24. Apparatus according to any of claims 20 to 23, wherein the actuator means are comprised within the body.

25. Apparatus according to any of claims 5 to 24, wherein the body comprises piezoelectric material.

26. Apparatus for printing on a substrate according to claim 20 or any claim dependent therefrom, comprising a plurality of openings for ejection of droplets from a respective

plurality of chambers, the plurality of openings being arranged in at least one linear array extending in the widthwise direction of the substrate and transversely to the direction of motion of the substrate relative to the apparatus, the support member extending over the entire width of the substrate.

27. Apparatus according to claim 20 or any claim dependent therefrom, comprising a plurality of openings for ejection of droplets from a respective plurality of chambers, the plurality of openings being arranged in at least one linear array extending in an array direction, wherein each chamber is formed as a channel having a longitudinal channel axis, the channel axis extending transversely to the array direction.

28. Apparatus according to claim 25, wherein an array of channels is formed in said body, successive channels in the array defining sidewalls therebetween, said sidewalls comprising piezoelectric material.

29. Method of manufacture of droplet deposition apparatus, the method comprising the steps of: providing a support member formed therein with at least one aperture and at least one conductive track; mounting on the support member a body formed with at least one chamber having an open side, the body also having actuator means associated with the chamber and responsive to electrical signals; the body being mounted such that the chamber is in registration with the at least one aperture and the actuator means are in registration with the conductive track; and mounting in registration with the conductive track a drive circuit for applying electrical signals to the actuator means, thereby to effect droplet ejection out of the chamber via the aperture.

30. Method according to claim 29, wherein a nozzle plate is attached to the opposite surface of the support member to that to which the body is attached and nozzles are

formed therein prior to the attachment of the body to the support member.

31. An electronic assembly comprising a substrate having electrically conductive tracks, there being a plurality of locations along each track at which an integrated circuit may be connected; the plurality of locations being spaced relative to one another along each track such that, for each track, a location lying adjacent a connection to an integrated circuit die falls outside the footprint of the integrated circuit die.

32. Method of changing the functionality of an electronic circuit comprising a substrate having electrically conductive tracks and a first integrated circuit mounted in a respective die connected to the tracks, the method comprising the steps of: connecting a second integrated circuit having a different functionality to that of the first integrated circuit to the tracks, connection being at locations on the tracks falling outside the footprint of the die of the first integrated circuit, and electrically isolating the first integrated circuit from the tracks.

1/8




*Fig. 1*

Fig. 2

3/8

*Fig. 3*

4/8




Fig. 4

5/8

Fig. 5







Fig. 6




6/8

Fig. 7

7/8

*Fig. 8*


*Fig. 9*



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B41J 2/16, 2/14, 2/045		A3	(11) International Publication Number: WO 98/52763
			(43) International Publication Date: 26 November 1998 (26.11.98)
(21) International Application Number: PCT/GB98/01495 (22) International Filing Date: 22 May 1998 (22.05.98) (30) Priority Data: 9710530.8 23 May 1997 (23.05.97) GB (71) Applicant (for all designated States except US): XAAR TECHNOLOGY LIMITED [GB/GB]; Science Park, Cambridge CB4 4FD (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): TEMPLE, Stephen [GB/GB]; 66 Ginton Road, Cambridge CB3 0LN (GB). (74) Agents: MOIR, Michael, Christopher et al.; Mathys & Squire, 100 Grays Inn Road, London WC1X 8AL (GB).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published With international search report. (88) Date of publication of the international search report: 18 March 1999 (18.03.99)	

(54) Title: DROPLET DEPOSITION APPARATUS AND METHODS OF MANUFACTURE THEREOF



(57) Abstract

Droplet deposition apparatus comprising first and second channels (82a, 82b), one end of each channel communicating with a single, common supply chamber (90) for supply of droplet liquid and the respective other ends of the first and second channels each communicating with a respective further supply chamber (88, 92) for supply of droplet liquid; each of said first and second channels having an opening (96a, 96b) for ejection of droplets therefrom; and actuator means being associated with each channel for effecting the ejection of droplets.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INTERNATIONAL SEARCH REPORT

In. onal Application No

PCT/GB 98/01495

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 B41J2/16 B41J2/14 B41J2/045

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B41J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 92 10367 A (MARKPOINT DEVELOPMENT AB) 25 June 1992 see the whole document ---	1-7, 11-16, 20,25-28
A	EP 0 628 413 A (CITIZEN WATCH CO.) 14 December 1994 see column 13, line 25 - column 14, line 25 see column 15, line 33 - line 44 see figures 11,17 ---	1-3,5,9, 11,12, 14,20, 29,30
A	EP 0 522 814 A (TOKYO ELECTRIC CO.) 13 January 1993 see the whole document -----	29,30



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

25 August 1998

Date of mailing of the international search report

09.12.98

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

V/D MEERSCHAUT, G

INTERNATIONAL SEARCH REPORT

International application No.

PCT/GB 98/ 01495

B x I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:

2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:

3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

SEE ANNEX

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.

2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.

3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:

4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

1-30

Remark on Protest

☐ The additional search fees were accompanied by the applicant's protest.

☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims : 1-30

The droplet deposition apparatus having a body with at least one ink channel, at least one ink supply chamber, actuator means associated with each channel, a cover for closing the open side of the at least one ink channel and having at least one opening for the ejection of droplets and a base.

2. Claims : 31-32

An electronic assembly comprising a substrate with electrically conductive tracks and a method of changing the functionality of an electronic circuit.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PL 1/GB 98/01495

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
WO 9210367	A	25-06-1992	DE	69011694 D	22-09-1994
			DE	69011694 T	26-01-1995
			EP	0560760 A	22-09-1993
			JP	6502810 T	31-03-1994

EP 628413	A	14-12-1994	JP	4241949 A	28-08-1992
			JP	4175167 A	23-06-1992
			EP	0627315 A	07-12-1994
			DE	69125098 D	17-04-1997
			DE	69125098 T	19-06-1997
			DE	69129159 D	30-04-1998
			DE	69129159 T	16-07-1998
			EP	0485241 A	13-05-1992
			US	5359354 A	25-10-1994

EP 522814	A	13-01-1993	JP	2744535 B	28-04-1998
			JP	5064893 A	19-03-1993
			DE	69205350 D	16-11-1995
			DE	69205350 T	15-05-1996
			KR	9603336 B	08-03-1996
			US	5193256 A	16-03-1993
